C class	Product Information
	GHP945BK
	NODEL
	MODEL
	Energy efficiency classes of domestic range hoods (A-G)
	Annual Energy Consumption - AEC hood (kWh/a)
	Fluid Dynamic Efficiency classes for domestic range hoods (A-G) Lighting Efficiency classes (A-G)
	The Grease Filtering Efficiency classes (A-G)
	Sound power level L WA - (dB)
	Time increase factor - f
	Fluid Dynamic Efficiency - FDE hood
	Energy Efficiency Index - EEI hood
	Measured air flow rate at best efficiency point - Q BEP (m 3 /h)
	Measured air pressure at best efficiency point P BEP (Pa)
	Measured electric power input at best efficiency point - W BEP (W)
	Nominal power of the lighting system - W L (W)
	Average illumination of the lighting system on the cooking surface - E middle (lux) Lighting
	Efficiency LE hood - (lux/Watt)
	Gerase Filtering Efficiency GFE hood - (%)
	Minimum airflow (Q min)
	Maximum air flow - Q max (m 3 /h)
	Airflow -boost (Q boost)
	Minimum sound power level LWA - (dB)
	Maximum sound power level LWA - (dB)
	Sound power level-boost L WA - (dB) Measured
	power consumption off mode P o (W)
	Measured power consumption in standby mode - P s (W)
	Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "

GHP945BK

С	
62.5	
С	
A	
С	
67	
1.3	
18.1	
73.2	
299.5	
259.6	
119.5	
8	
498.11	
62.26	
78	
379.62m ³ /h	
501.54m ³ /h	
-	
62dB	
67dB	
-	
0	
0	